

Attachment

Main Specifications of Xi™ Data Terminals

(Subject to change)

L-09C

Height x Width x Thickness		122 x 64 x 15.9 mm
Weight		156 grams
Network side	Xi LTE	Max. 37.5 Mbps downlink, 12.5 Mbps uplink
	FOMA 3G	FOMA HIGH-SPEED (incl. FOMA Plus-Area): Max. 7.2 Mbps downlink, 5.7 Mbps uplink
Device-side Wireless Standard		IEEE802.11b/g/n
Interface		microSDHC™ memory card (32 GB) microSD™ 2.0 memory card (High Speed)
Simultaneous Connection		Up to 10 devices
Continuous Stand-by Time (static)		35 hours
Continuous Connection Time		8 hours (3G) / 6 hours (LTE)
Color		White

BF-01C

Height x Width x Thickness		64.4 x 95.0 x 17.4 mm
Weight		130 grams
Network side	Xi LTE	Max. 37.5 Mbps downlink, 12.5 Mbps uplink
	FOMA 3G	FOMA HIGH-SPEED (incl. FOMA Plus-Area): Max. 7.2 Mbps downlink, 5.7 Mbps uplink
	Wireless Standard	IEEE802.11a/b/g/n
	Wired Standards (cradle provided)*	IEEE802.3u (100BASE-TX) IEEE802.3 (10BASE-T)
Device side	Wireless Standard	IEEE802.11b/g/n
	Wired Standards *	IEEE802.3u (100BASE-TX) IEEE802.3 (10BASE-T)
Interface		None (connects to Ethernet cradle)
Simultaneous Connection		Up to 6 devices
Continuous Stand-by Time (static)		30 hours
Continuous Connection Time		6 hours (3G) / 4 hours (LTE)
Color		White

*Must be used either for network or device only, activated by switch on cradle.